

D-ATIS
 118.0 257.7
 CLNC DEL
 119.2 259.3
 CPDLC
 GND CON
 121.9 348.6
 ALBUQUERQUE TOWER
 120.3 351.9
 ALBUQUERQUE DEP CON
 123.9 354.1


SW-1, 19 FEB 2026 to 19 MAR 2026

**TOP ALTITUDE:
 FL200**

TAKEOFF MINIMUMS

Rwy 3: Standard with minimum climb of 500' per NM to 9000.
 Minimum obstacle climb gradient after YUGLU is 420' per NM to 11900.
 Rwy 8: Standard with minimum climb of 515' per NM to 9000.
 Minimum obstacle climb gradient after YUGLU is 420' per NM to 11900.

NOTE: Takeoff Rwy 3, do not exceed 220K until passing 6000.
 NOTE: Takeoff Rwy 8, do not exceed 220K until passing 5860.
 NOTE: Do not exceed 250K until passing MNZNO.
 NOTE: DME/DME/IRU or GPS required.
 NOTE: For turbojet aircraft only.
 NOTE: RNAV 1.
 NOTE: RADAR required.
 NOTE: If unable to accept climb gradient, advise ATC on initial contact.
 NOTE: For non-GPS equipped aircraft ONM DME must be operational.



(NARRATIVE ON FOLLOWING PAGE)

NOTE: Chart not to scale.

SW-1, 19 FEB 2026 to 19 MAR 2026



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 3: Climb heading 034° to 6000, then right turn direct DLSOL, then on track 173° to YUGLU, cross YUGLU at or below 9000, then on depicted route to MNZNO, cross MNZNO at or above 11500. Thence

TAKEOFF RUNWAY 8: Climb heading 079° to 5860, then right turn direct DLSOL, then on track 173° to YUGLU, cross YUGLU at or below 9000, then on depicted route to MNZNO, cross MNZNO at or above 11500. Thence

. . . . (transition). Maintain FL200, expect filed altitude ten minutes after departure.

- CHISUM TRANSITION (MNZNO3.CME)
- LAMSE TRANSITION (MNZNO3.LAMSE)
- MOLVE TRANSITION (MNZNO3.MOLVE)
- SOCORRO TRANSITION (MNZNO3.ONM)
- ST JOHNS TRANSITION (MNZNO3.SJN)
- TEXICO TRANSITION (MNZNO3.TXO)

SW-1, 19 FEB 2026 to 19 MAR 2026

SW-1, 19 FEB 2026 to 19 MAR 2026